

## KV394N

Hood, Decorative wall hood, Universale, Black, 90 cm, A



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 90 cm • Extraction: Extraction • Electronic control: Yes • Perimeter extraction: Yes • EAN code: 8017709305758

### AESTHETICS

Colour: Black • Finishing: Glass • Aesthetics: Universale • Design: Angled • Material: Glass • Glass Type: Black

### PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • 24h air filter function: Yes • Time-setting options: Automatic switch-off • Auto-vent 2.0: Sì

### CONTROLS

Control setting: Touch control back-lighted White • Led color: White

## TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1,1 W • Dimmer mode: Yes • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 730 m<sup>3</sup>/h • Motor power: 230 W • No. of filters: 2 • Anti-grease filters: Aluminium • Charcoal filters included: Yes • Filter replacement indicator: Yes • Minimum distance from GAS hob: 650 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 450 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEC<sub>hood</sub>): 53 kWh/a • Fluid Dynamic Efficiency (FDE): 31.4 • Lighting Efficiency (LE): 118.5 lux/W • Grease Filtering Efficiency (GFE): 73.8 % • Air flow at minimum speed (Q<sub>min</sub>): 285 m<sup>3</sup>/h • Air flow at maximum speed (Q<sub>max</sub>): 493 m<sup>3</sup>/h • Air flow at boost speed (Q<sub>boost</sub>): 729 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 47 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 61 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 69 dB(A) • Power Consumption in Off mode (P<sub>o</sub>): 0.49 W • Power consumption in stand-by mode (P<sub>s</sub>): 0.99 W • Time increase factor (F): 0.9 • Energy Efficiency Index: 51.6 • Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 397 m<sup>3</sup>/h • Measured air pressure at best efficiency point (P<sub>bep</sub>): 443 Pa • Measured electric power input at best efficiency point (W<sub>bep</sub>): 155 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (E<sub>middle</sub>): 237 lux • Sound power level at highest setting (L<sub>wa</sub>): 61 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 232 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

## OPTIONAL ACCESSORIES

### SPEED 1

Extraction rate IEC 61591: 285 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 47 dB(A) • Power: 145 W

### SPEED 2

Extraction rate IEC 61591: 374 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 54 dB(A) • Power: 163 W

### SPEED 3

Extraction rate IEC 61591: 493 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 60 dB(A) • Power: 186 W

### SPEED 4

## INTENSIVE SPEED

Extraction rate (IEC 61591): 729 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 69 dB(A) • Power: 230 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 459x895x439 • Width: 895 mm • Depth (mm): 439 mm • Product Height (mm): 459 mm • Net weight (kg): 20.080 kg • Gross weight (kg): 24.700 kg

## OPTIONAL

KITALLFC: Charcoal filter, HoodsFLT6: Charcoal filter, Hoods

